

RLS27

REDLIFT

MASTER THE HEIGHTS

Métallomax



THE REDLIFT DISTINCTION



LATERAL FLOOR EXTENSION

- Only platform on the market with a CSA-approved lateral floor extension, an additional work area that significantly improves versatility and productivity, available as an option on all models



4 DIRECTIONAL WHEELS

- Experience the unparalleled control and manoeuvrability of independent front and rear directional wheels, a unique Redlift feature standard on all models



SELF-LEVELING STABILIZERS

- Improve stability at heights thanks to 4 stabilizers with both self-levelling and independent control, for ease of use or total control over any type of terrain

2-YEAR WARRANTY




REDLIFT | 21, Gauthier street, Warwick (Québec) J0A 1M0, Canada
Telephone : 819 358-6999 | info@redlift.ca | redlift.ca



SPECIFICATIONS

Platform Height	309 in
Max Work Height	381 in
Platform Capacity	1500 lb
Deck Extension Capacity	275 lb
Lateral Floor Capacity	420 lb
Lift / Lower Time	27 s
Machine Weight	8810 lb
Drive Speed	4 km/h
Turning Radius (Inside)	66 in
Turning Radius (Outside)	126 in
Diesel Engine	Kubota D1105 24,5hp (Tier 4)
Tires	27 in (10,50 X 15)
Hydraulic Brakes	4 wheels
Hydraulic Tank Capacity	125 L
Fuel Tank Capacity	125 L
Max Tilt Rating (Fore and Aft)	3°
Max Tilt Rating (Side-to-Side)	3°

DIMENSIONS



A	Overall Length	148 in	F	Rails Height	43,5 in
B	Wheelbase	95,2 in	G	Platform Area	148 po X 68 in
C	Overall Width	78 in	H	Extension Deck	36 in
D	Overall Height - Rails up	105 in	I	Sidebars	24 in
E	Platform Height - Stowed	60 in	J	Ground Clearance	10 in

REDLIFT

RLS27

Redlift is imposing itself on the market and inspires many passions. Thanks to Redlift, you can now count on impeccable Workmanship and unparalleled performance. Redlift ensures its aerial platforms rise to meet your highest standards.

Go on, master the heights!



- Only platform on the market allowing installation of a 24-inch wide lateral floor for more ergonomy and versatility
- 4 directional wheels give Redlift unparalleled manoeuvrability on construction sites
- A 5,5" color screen allows easy diagnostics for quick turnaround in case of breakdowns
- Powerful disengageable planetary gearbox traction guarantees mobility in all types of terrain

STOCK EQUIPMENT

- 4 wheel drive and directional wheels
- 68" x 145" steel structure deck
- 36" front deck extension
- 2 proportional speeds
- 24" lateral floor supports
- Collapsible guard rails
- Lockable electric and hydraulic compartments
- Lockable diesel and oil reservoirs
- Independent stabilizers with self-levelling function and ground contact LED indicator
- Removable control station with quick-connect
- Safety support strut for maintenance and inspection
- 4,75" non-slip access ladder
- 110V outlet on deck
- Horn and travel alarm
- Tilt alarm
- Strobe light
- Engine block heater
- Oil heater

OPTIONAL

- + 12' lateral floor with guard rails
- + 36" rear deck extension
- + Catalyzed muffler
- + Foam-filled tires

REDLIFT
MASTER THE HEIGHTS